

Timken 495/493 tapered roller bearings

Timken 495/493 tapered roller bearings Engineering Calculator , C 3156 K Bearing (basic designation) Manufacturing Service . 0H 3156 HTL Adapter sleeve Get Your Free.

Bearing (basic designation)	C 3156 K
Adapter sleeve	0H 3156 HTL
Locating ring	2 x FRB 10/460
da	260 mm
Ca	166 mm
Da	460 mm
A	315 mm
A1	280 mm
H	551 mm
H1	280 mm
H2	105 mm
J	670 mm
J1	160 mm
L	790 mm
N	50 mm
N1	42 mm
s	16 mm
ba min.	119 mm
ba max.	149 mm
bb	114 mm
bc	154.5 mm
J6	740 mm

N4 max.	20 mm
Oil seal	TSD 3156 U
End cover	ETS 3156 R
P0°	4000 kN
P55°	5000 kN
P90°	2400 kN
P120°	1800 kN
P150°	1600 kN
P180°	2000 kN
Pa	1300 kN
Q120°	2860 kN
Q150°	1650 kN
Q180°	1430 kN
Mass housing	252 kg
Cap bolt, size	M 30×200
Cap bolt, rec. tightening torque	400 N·m
Appropriate attachment bolt, size G	36 mm
Appropriate attachment bolt, rec. tightening torque	2280 N·m
Eye bolt, size	2 x M 24
Oil level, min.	74 mm
Oil level, max.	92 mm