

Timken 5218WD angular contact ball bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products at Low 160 mm Da Costs. 82.55 mm da

da	82.55 mm
Da	160 mm
Ca	49.809 mm
A1	98.425 mm
A2	149.225 mm
S	4.763 mm
ba	40.481 mm
H	192.484 mm
H1	101.6 mm
H2	41.275 mm
J min.	260.35 mm
J max.	298.45 mm
L	349.25 mm
N1	22.225 mm
R1	60.325 mm
R2	27.781 mm
RG	3/8 NPT
PG	1/8 NPT
h	38.1 mm
Housing	SAF 518
Bearing	22218 EK
Adapter sleeve assembly	SNW 18×3.1/4
Stabilizing ring	SR-18-15

Labyrinth ring	2 x LOR 187
End plug (suffix Y)	EPR 11
Bearing limiting speed	5300 r/min
P60°	121 kN
P90°	72.5 kN
P120°	45.4 kN
P150°	40.5 kN
P180°	49.8 kN
Pa	10.9 kN
Mass pillow block	21.4 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	141.75 g