

Timken 565/563 tapered roller bearings

What is Timken 565/563 tapered roller bearings in mechanical engineering? Manufacturing Service . 41,275 Outer Diameter (mm) Upload your 73.431×41.275×21.43 Size (mm) CAD 73,431 Bore Diameter (mm) file for an instant.

Size (mm)	73.431×41.275×21.43
Bore Diameter (mm)	73,431
Outer Diameter (mm)	41,275
Width (mm)	21,43
d	41.275 mm
D	73.431 mm
T	21.43 mm
d1	57.8 mm
B	19.812 mm
C	16.604 mm
r1,2 – min.	3.5 mm
r3,4 – min.	0.8 mm
a	18 mm
da – max.	48 mm
db – min.	52.5 mm
Da – min.	63 mm
Da – max.	68 mm
Db – min.	69 mm
Ca – min.	3 mm
Cb – min.	4.5 mm
ra – max.	3.3 mm

rb – max.	0.8 mm
Basic dynamic load rating – C	55 kN
Basic static load rating – C0	68 kN
Fatigue load limit – Pu	7.6 kN
Reference speed	6700 r/min
Limiting speed	10000 r/min
Calculation factor – e	0.4
Calculation factor – Y	1.5
Calculation factor – Y0	0.8
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.355
Product Group	B04334