

Timken 59176/59425 tapered roller bearings

Timken 59176/59425 tapered roller bearings Warehouse offers car parts 47 Outer Diameter (mm) and 20x47x14 Size (mm) car 20 Bore Diameter (mm) accessories. We sell discount online as well as cheap machinery parts.

Size (mm)	20x47x14
Bore Diameter (mm)	20
Outer Diameter (mm)	47
Width (mm)	14
d	20 mm
D	47 mm
B	14 mm
C	14 mm
r min.	1 mm
da min.	25 mm
da max	26,5 mm
Da max.	42 mm
ra max.	1 mm
Weight	0,107 Kg
Basic dynamic load rating (C)	12,8 kN
Basic static load rating (C0)	6,6 kN
(Grease) Lubrication Speed	15 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.05

EAN	0029176014291
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6204ZZ
Weight / LBS	0.105
Bore	0.787 Inch 20 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.551 Inch 14 Millimeter
bore diameter:	20 mm
static load capacity:	6600 N
outside diameter:	47 mm
precision rating:	ABEC 1 (ISO Class Normal)
overall width:	14 mm
finish/coating:	Uncoated

bore type:	Round
cage material:	Steel
closure type:	Double Shielded
outer ring width:	14 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
internal clearance:	C0
maximum rpm:	18000 RPM
operating temperature range:	-10 to +110 °C
series:	62
dynamic load capacity:	12800 N
SRI	4.01
hidYobi	6204ZZ
LangID	1
D_	47
SREX	0.04
B_	14
da min	25
hidTable	ecat_NSRDGB
SRE	4.21
mass	0.107
GRS rpm	15000
ra	1
SRIX	0.02
D_a	42
SRIN	0
C0	6.6
fo	13.1
SREN	0

DE_	41.438
Prod_Type3	DGBB_SR_ZZ
DA_	7.938
bomp	0
Z_	8
yobi	6204ZZ
C_conv	12800
ALPHA_	0
SDM_	33.5
r	1
KBRG	6141
SBRG	2
DI_	25.562