Timken 593/592D+X2S-593 tapered roller bearings

Offer High Quality Brand Timken 593/592D+X2S-593 tapered roller bearings .Contact Us 1-1/4 in d Online to Get Best 2.8750 in D Quote.

d	1-1/4 in
locking device:	Double Concentric Collar
D	2.8750 in
expansion type:	Non-Expansion Bearing (Fixed)
В	4.0000 in
seal type:	Contact/Lip
overall height:	4 in
overall depth:	2-13/16 in
flange mounting type:	Four-Bolt Square
radial dynamic load capacity:	2975 lb
bearing type:	Tapered Roller
<pre>bearing type: operating temperature range:</pre>	Tapered Roller -20 to +220 °F
operating temperature range:	-20 to +220 °F
operating temperature range: housing construction:	-20 to +220 °F Solid Flange Mount
operating temperature range: housing construction: finish/coating:	-20 to +220 °F Solid Flange Mount Fluoropolymer
<pre>operating temperature range: housing construction: finish/coating: bore type:</pre>	-20 to +220 °F Solid Flange Mount Fluoropolymer Round
operating temperature range: housing construction: finish/coating: bore type: lubrication type:	-20 to +220 °F Solid Flange Mount Fluoropolymer Round Lubrication Fitting
<pre>operating temperature range: housing construction: finish/coating: bore type: lubrication type: duty type:</pre>	-20 to +220 °F Solid Flange Mount Fluoropolymer Round Lubrication Fitting Air Handling