## Timken 594/592D+X3S-594 tapered roller bearings

Timken 594/592D+X3S-594 tapered roller bearings ABB MOTORS AND MECHANICAL INC Manufacturer Name 0.0 Inventory with easy-to-use parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC                  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 13.166   |
| EAN                       | 0782476587734                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 4 Bolt Pillow Block                            |
| Rolling Element           | Tapered Roller Bearing                         |
| Housing Material          | Cast Iron                                      |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 5/8 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | S1U-EXL-204R                                   |
| Seals                     | Triple Lip Contact                             |
| Housing Configuration     | 2 Piece Split                                  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw |

| Long Description                 | 4 Bolt Pillow Block; 2-1/4" Bore; 2-3/4" Base to Center Height; Concentric Collar Mount; T |
|----------------------------------|--|
| UNSPSC                           | 31171511   |
| Harmonized Tariff Code           | 8483.20.40.80  |
| Noun                             | Bearing  |
| Keyword String                   | Pillow Block   |
| Manufacturer Item Number         | P4B-EXL-204R   |
| Manufacturer Internal Number     | 077267   |
| Weight / LBS                     | 29   |
| D                                | 4 Inch   101.6 Millimeter  |
| Bolt Spacing Minimum             | 7.75 Inch   196.85Millimeter   |
| d                                | 2.25 Inch   57.15 Millimeter   |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter   |
| В                                | 2.75 Inch   69.85 Millimeter   |
| Nominal Bolt Center to<br>Center | 7.9 Inch   199.5 Millimeter  |
| Bolt Spacing Maximum             | 8.25 Inch   209.55Millimeter   |