

# Timken 595/592XS tapered roller bearings

What are the types of Timken 595/592XS tapered roller bearings ? 0.0 Inventory Manufacturing Service . Get Your Free, Instant price, design review.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.522   |
| EAN                       | 0883450229432  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22219  |
| Seals                     | Triple Lip Urethane  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Nut  |
| Long Description          | 4 Bolt Pillow Block; 3-3/16" Bore; 3-3/4" Base to Center Height; V Lock Mount; Spherical R |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QVVPR19V303S0                  |
| Weight / LBS                  | 49                             |
| B                             | 3.75 Inch   95.25 Millimeter   |
| Bolt Spacing Maximum          | 11.25 Inch   285.75Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| D                             | 4.63 Inch   117.602 Millimeter |
| Bolt Spacing Minimum          | 9.25 Inch   234.95Millimeter   |
| d                             | 3.188 Inch   80.975 Millimeter |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter   |