

Timken 60RIU250 cylindrical roller bearings

Browse 140 Outer Diameter (mm) Timken 60RIU250 cylindrical roller bearings Categories in the Manufacturers Online 300x140x62 Size (mm) Free. including 300 Bore Diameter (mm) .

Size (mm)	300x140x62
Bore Diameter (mm)	300
Outer Diameter (mm)	140
Width (mm)	62
d	140 mm
D	300 mm
B	62 mm
D1	251.7 mm
F	180 mm
r1,2 – min.	4 mm
r3,4 – min.	4 mm
s	3.7 mm
da – min.	157 mm
da – max.	175 mm
db – min.	183 mm
Da – max.	282.5 mm
ra – max.	3 mm
rb – max.	3 mm
Basic dynamic load rating – C	780 kN
Basic static load rating – C0	830 kN
Fatigue load limit – Pu	88 kN
Reference speed	2400 r/min

Limiting speed	4300 r/min
Calculation factor – kr	0.23
D1 ≈	251.7 mm
r1,2 min.	4 mm
r3,4 min.	4 mm
s max.	3.7 mm
da min.	157 mm
da max.	175 mm
db min.	183 mm
Da max.	282.5 mm
ra max.	3 mm
rb max.	3 mm
Basic dynamic load rating C	780 kN
Basic static load rating C0	830 kN
Fatigue load limit Pu	88 kN
Calculation factor kr	0.23
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	22 kg
Angle ring	HJ 328 EC