

Timken 67391/67322D+X1S-67390 tapered roller bearings

Timken 67391/67322D+X1S-67390 tapered roller bearings Engineering 15 mm d Calculator , Manufacturing Service . Get Your 14 mm B Free.

d	15 mm
D	28 mm
B	14 mm
C	13 mm
F	20 mm
rs min	0.3 mm
Dw	2.5 mm
Lw	7.8 mm
Lubrication hole on outer ring	Oui/Yes
k	2.5 mm
Lubrication hole on inner ring	Oui/Yes
Radial clearance class	CN
Precision class	P0
Mass	0.04 kg
Cr	8.3 kN
C0r	11.2 kN
Nlim (grease)	10,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.89 Hz
Characteristic outer ring frequency, BPF0	7.56 Hz

Characteristic inner ring frequency, BPFI	9.44 Hz
da min	17 mm
Da max	22 mm
Db max	26 mm
ras max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.044
Product Group	B04144