

Timken

67787/67720CD+X2S-67787

tapered roller bearings

Our highly-skilled and factory-trained service 0.0 Inventory experts have the resources to help you with all your Timken 67787/67720CD+X2S-67787 tapered roller bearings SKF Manufacturer Name needs – including routine maintenance, major repairs, warranty service, and N/A Minimum Buy Quantity equipment inspections.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.517
EAN	7316577652157
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C4-Extra Loose
Retainer	Yes
Relubricatable	Yes

Inch – Metric	Metric
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	40MM Bore; Straight Bore Profile; 80MM Outside Diameter; 23MM Width; Polymer Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NJ 2208 ECP/C4
Weight / LBS	1.138
d	1.575 Inch 40 Millimeter
D	3.15 Inch 80 Millimeter
B	0.906 Inch 23 Millimeter
bore diameter:	40 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	80 mm
maximum rpm:	11000 RPM
overall width:	23 mm
bearing material:	Steel
flanges:	(2) Outer Ring, (1) Inner Ring
cage material:	Polyamide
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C4

application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	23 mm
operating temperature range:	Maximum of +300 °F
fillet radius:	1 mm
dynamic load capacity:	81.5 kN
series:	NJ22
static load capacity:	75 kN