

# Timken 679/672D+X2S-679 tapered roller bearings

With over 10170 full-service stores, our Timken 679/672D+X2S-679 tapered roller bearings inventory is extensive and our parts 120x180x28 Size (mm) are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Size (mm)	120x180x28
Bore Diameter (mm)	120
Outer Diameter (mm)	180
Width (mm)	28
d	120 mm
D	180 mm
B	28 mm
C	28 mm
r min.	2 mm
da min.	129 mm
da max	134,5 mm
Da max.	171 mm
ra max.	2 mm
Weight	2,08 Kg
Basic dynamic load rating (C)	88 kN
Basic static load rating (C0)	80 kN
(Grease) Lubrication Speed	3 600 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A

Weight / Kilogram	2
EAN	0029176078682
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	120MM Bore; 180MM Outside Diameter; 28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; N
Other Features	Deep Groove   Rubber Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	4.5864
Bore	4.724 Inch   120 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	7.087 Inch   180 Millimeter
Outer Race Width	1.102 Inch   28 Millimeter
SRI	9.86
hidYobi	6024VV
LangID	1

D_	180
SREX	0.04
B_	28
da min	129
hidTable	ecat_NSRDGB
SRE	9.86
mass	2.08
GRS rpm	3600
ra	2
SRIX	0.04
D_a	171
SRIN	-0.04
C0	80
fo	15.7
SREN	-0.04
DE_	169.05
Prod_Type3	DGBB_SR_VV
DA_	19.05
bomp	0
Z_	14
yobi	6024VV
C_conv	88000
ALPHA_	0
SDM_	150
r	2
KBRG	6151
SBRG	10
DI_	130.95