

Timken 9113P deep groove ball bearings

170 Million used Timken 9113P deep groove ball bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and location. Order 103.188 mm da the with stock ...

da	103.188 mm
Da	215.001 mm
Ca	67.793 mm
A1	120.65 mm
A2	187.325 mm
S	4.763 mm
ba	53.181 mm
H	257.175 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	46.831 mm
Housing	SAF 524

Bearing	22224 EK
Adapter sleeve assembly	SNW 24×4.1/16
Stabilizing ring	SR-24-20
Labyrinth ring	2 x LOR 111
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1350 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	20.7 kN
Mass pillow block	47.2 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g