

Timken

94700/94114CD+X6S-94700

tapered roller bearings

YOU'LL FIND 0.0 Inventory N/A Minimum Buy Quantity AN EXTENSIVE SKF Manufacturer Name SELECTION OF Timken 94700/94114CD+X6S-94700 tapered roller bearings FOR SALE.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	9.99
EAN	7316576668111
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Tapered Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	1213 EK
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row Medium Duty

Long Description	2 Bolt Pillow Block; 2-3/16" Bore; 3" Base to Center Height; Tapered Adapter Sleeve Mount;
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 1513
Weight / LBS	22
Bolt Spacing Minimum	8.125 Inch 206.375Millimeter
B	3 Inch 76.2 Millimeter
Nominal Bolt Center to Center	8.8 Inch 223 Millimeter
d	2.188 Inch 55.575 Millimeter
D	4.5 Inch 114.3 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Maximum	9.5 Inch 241.3Millimeter
bore diameter:	2.1875 in
overall width:	4.5000 in
overall length:	11.0000 in
seal type:	Labyrinth Seal
overall height:	5.8125 in
base height:	1.0000 in
mounting:	Two-Bolt Base
maximum operating temperature:	Max 210 °F
bearing type:	Spherical Roller
maximum rpm:	7000 rpm
bore type:	Round
lubrication type:	Lubrication Fitting

housing construction:	Split Pillow Block
bolt size:	0.7500 in
base to bore centerline:	3.0000 in
series:	SAF1513
housing material:	Cast Iron
replacement bearing:	1213 EKTN9
locking device:	Adapter Mount
weight:	23.1 lbs
bearing material:	Cast Iron
manufacturer product page:	Click here
finish/coating:	Blue Alkyd/Acryl Paint (RAL 5001)
manufacturer upc number:	7316576668111
da	55.563 mm
Da	120 mm
Ca	39.014 mm
A1	79.375 mm
A2	114.3 mm
ba	27.781 mm
H	147.637 mm
H1	76.2 mm
H2	25.4 mm
J min.	206.375 mm
J max.	241.3 mm
L	279.4 mm
N1	19.05 mm
R1	44.45 mm
R2	15.875 mm
RG	1/8 NPT

PG	1/8 NPT
h	30.163 mm
Housing	SAF 513
Bearing	1213 EKTN9
Adapter sleeve assembly	SNW 13×2.3/16
Stabilizing ring	2 x SR-13-0
Labyrinth ring	2 x LER 29
End plug (suffix Y)	EPR 6
Bearing limiting speed	7000 r/min
P60°	50.3 kN
P90°	30.2 kN
P120°	17.8 kN
P150°	16 kN
P180°	19.1 kN
Pa	4.45 kN
Mass pillow block	10.5 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	81.3 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	107.73 g