

# Timken A6075/A6157B tapered roller bearings

Offer High 95 Bore Diameter (mm) Quality 95x170x32 Size (mm) Brand Timken A6075/A6157B tapered roller bearings 170 Outer Diameter (mm) .Contact Us Online to Get Best Quote.

Size (mm)	95x170x32
Bore Diameter (mm)	95
Outer Diameter (mm)	170
Width (mm)	32
d	95 mm
Fw	113,5 mm
D	170 mm
B	32 mm
C	32 mm
r min.	2,1 mm
r1 min.	2,1 mm
Weight	2,78 Kg
Basic dynamic load rating (C)	166 kN
Basic static load rating (C0)	195 kN
(Grease) Lubrication Speed	4 000 r/min
E	151.5 mm
F	113.5 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	CN
Mass (without HJ ring)	2.78 kg
Dynamic load, C	166 kN

Static load, C0	195 kN
Fatigue limit load, Cu	21.9 kN
Nlim (oil)	4,700 rpm
Nlim (grease)	4,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	106 mm
da max	111 mm
db min	116 mm
Da max	159 mm
ra max	2 mm
rla max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359000542
Product Group	B04144
bore diameter:	95 mm
static load capacity:	195000 N
outside diameter:	170 mm
precision rating:	ISO Class 0
overall width:	32 mm
maximum rpm:	4700 rpm
flanges:	(2) Outer Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	Pressed Steel
number of rows:	1

finish/coating:	Uncoated
internal clearance:	CN
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	2 mm
operating temperature range:	-40 to 120 °C
manufacturer product page:	<a href="#">Click here</a>
dynamic load capacity:	166000 N