

Timken AX 6 65 90 needle roller bearings

Find the discount Timken AX 6 65 90 needle roller bearings 95x145x24 Size (mm) online you need . We offer ... If you check out our large selection of Timken AX 6 65 90 needle roller bearings once .

Size (mm)	95x145x24
Bore Diameter (mm)	95
Outer Diameter (mm)	145
Width (mm)	24
d	95 mm
D	145 mm
B	24 mm
C	24 mm
a	3.71 mm
b	3.1 mm
f	2.82 mm
r min.	1.5 mm
r1 min.	0.5 mm
D1	140.23 mm
D2	154.7 mm
Weight	1.16 Kg
Basic dynamic load rating (C)	60,5 kN
Basic static load rating (C0)	54 kN
(Grease) Lubrication Speed	4500 r/min
Inventory	0.0
Manufacturer Name	NACHI

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	95MM Bore; 145MM Outside Diameter; 24MM Outer Race Width; 1 Metal Shield; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove With Snap Ring
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Outside Diameter	5.709 Inch 145 Millimeter
Bore	3.74 Inch 95 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.945 Inch 24 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	95 mm
Width	24 mm
Fillet Radius/Chamfer	1.5 mm

r1	0.5 mm
Snap Ring Width	2.8 mm
Snap Ring Outside Diameter	154.7 mm
D1 (max)	140.2 mm
a (max)	3.7 mm
b (min)	3.1 mm
Dynamic Load Rating	60,500 N
Static Load Rating	54,000 N
Limiting Speed – Grease	4,500 rpm
Limiting Speed – Oil	5,300 rpm
Factor fo	15.8
Radial Clearance	0.012 to 0.036 mm
da (min)	102 mm
Da (max)	138 mm
Dx (min)	157 mm
ra (max)	1.5 mm
Cy (max)	6.1 mm