

# Timken

## EE275095/275161D+X3S-275095

### tapered roller bearings

Shop Timken EE275095/275161D+X3S-275095 tapered roller bearings huge online discount inventory. N/A Minimum Buy Quantity and Import machinery parts your TIMKEN Manufacturer Name car needs with 0.0 Inventory Free Shipping and Free Extended Warranty.

|                           |                               |
|---------------------------|-------------------------------|
| Inventory                 | 0.0                           |
| Manufacturer Name         | TIMKEN                        |
| Minimum Buy Quantity      | N/A                           |
| Weight                    | 5.902                         |
| EAN                       | 0883450140430                 |
| Product Group             | M06288                        |
| Number of Mounting Holes  | 4                             |
| Mounting Method           | V Lock                        |
| Housing Style             | 4 Bolt Round Flange Cartridge |
| Rolling Element           | Spherical Roller Bearing      |
| Housing Material          | Cast Steel                    |
| Expansion / Non-expansion | Expansion                     |
| Mounting Bolts            | 1/2 Inch                      |
| Relubricatable            | Yes                           |
| Insert Part Number        | 22212                         |
| Seals                     | Double Lip Viton              |
| Housing Configuration     | 1 Piece Solid                 |
| Pilot Configuration       | With Pilot                    |
| Inch – Metric             | Inch                          |

|                                       |   |
|---------------------------------------|---|
| Long Description                      | 4 Bolt Round Flange Cartridge;<br>2-1/4" Bore; 5.9" Bolt Circle;<br>4.24" Bolt Spacing; 1 P |
| Other Features                        | Double Row   Single Nut   |
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.80   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Weight / LBS                          | 13  |
| Cartridge Pilot Diameter              | 5 Inch   127 Millimeter   |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter   |
| d                                     | 2.25 Inch   57.15 Millimeter  |
| D                                     | 3.14 Inch   79.756 Millimeter   |
| Nominal Bolt Circle Diameter<br>Round | 5.9 Inch   150 Millimeter   |
| Bolt Spacing                          | 4.24 Inch   107.7 Millimeter  |