Timken GE110SX plain bearings

offers a Timken GE110SX plain bearings selection of Genuine $39\times42.862\times14$ Size (mm) at Wholesale Prices. We are a Timken GE110SX plain bearings Certified Parts Retailer

| Size (mm) | 39×42.862×14 |
|--|--------------|
| Bore Diameter (mm) | 39 |
| Outer Diameter (mm) | 42,862 |
| Width (mm) | 14 |
| d | 42.862 mm |
| A1 | 39 mm |
| A2 | 14 mm |
| J | 105 mm |
| L | 137 mm |
| Т | 54.2 mm |
| Н | 15.9 mm |
| В | 49.2 mm |
| s1 | 30.2 mm |
| Basic dynamic load rating — C | 33.2 kN |
| Basic static load rating — CO | 21.6 kN |
| Limiting speed | 140 r/min |
| Limiting temperature — T | 350 °C |
| Mass bearing unit | 2.25 kg |
| Grub (set) screw — G2 — 5/16-24 UNF | 5/1624 UNF |
| Hexagonal key size for grub screw — H | 3.969 mm |
| Recommended tightening torque for grub screw | 6.5 N·m |

| Inventory | 0.0 |
|---------------------------|---|
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 2.23 |
| EAN | 7316571381251 |
| Product Group | M06110 |
| Number of Mounting Holes | 4 |
| Mounting Method | Set Screw |
| Housing Style | 4 Bolt Square Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 9/16 Inch |
| Relubricatable | Yes |
| Insert Part Number | YAR 209-111-2FW/VA228 |
| Seals | M Seal |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch — Metric | Inch |
| Long Description | 4 Bolt Square Flange Block; 1-11/16" Bore; 5.8" Bolt Circle; 4-1/8" Bolt Spacing; 1 P |
| Other Features | Single Row Standard Duty Wide Inner Race Open End High Temperature Bearing with Graphite H |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| | |

| Keyword String | Flanged |
|---------------------------------------|-----------------------------------|
| Manufacturer Item Number | FY 1.11/16 TF/VA228 |
| Weight / LBS | 4.9 |
| Nominal Bolt Circle Diameter Round | 5.8 Inch 148 Millimeter |
| Bolt Spacing | 4.125 Inch 104.78 Millimeter |
| Bore | 1.688 Inch 42.875 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Length Thru Bore | 1.938 Inch 49.225 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| bore diameter: | 1.6875 in |
| radial static load capacity: | 4860 lbf |
| bolt center-to-center length: | 105 mm |
| seal type: | Contact Seal |
| overall length/diameter: | 137 mm |
| length through bore: | 54.2 mm |
| bore type: | Round |
| operating temperature range: | -30 to +120 °F |
| mounting type: | Four-Bolt Flange |
| finish/coating: | Uncoated |
| housing material: | Cast Iron |
| lubrication type: | Cannot Be Relubricated |
| locking device: | Set Screw |
| series: | FY |
| expansion type: | Non-Expansion Bearing (Fixed) |
| manufacturer upc number: | 7316571381251 |

| N | 15.9 mm |
|---|-----------------------|
| Basic dynamic load rating C | 33.2 kN |
| Basic static load rating CO | 21.6 kN |
| Limiting temperature T max. | 350 °C |
| Grub (set) screw G2 | 5/16-24 UNF |
| Hexagonal key size for grub screw N | 3.969 mm |
| Attachment bolts, recommended metric size G | 14 mm |
| Bearing | YAR 209-111-2FW/VA228 |