

# Timken H414235/H414210-B tapered roller bearings

Timken H414235/H414210-B tapered roller bearings Warehouse offers car 0.0 Inventory parts and car N/A Minimum Buy Quantity accessories. We sell discount SKF Manufacturer Name online as well as cheap machinery parts.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | SKF  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 20.2   |
| EAN                       | 7316576674983  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22220  |
| Seals                     | Trigard  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Heavy Duty  <br>Locating Bearing   Open End  <br>With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 3-11/16" Bore; 4-1/8" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | SYR 3.11/16 H  |
| Weight / LBS                  | 44.5   |
| B                             | 4.125 Inch   104.775 Millimeter  |
| Nominal Bolt Center to Center | 10.9 Inch   276.9 Millimeter   |
| Bolt Spacing Minimum          | 10 Inch   254Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 4.594 Inch   116.688 Millimeter  |
| d                             | 3.688 Inch   93.675 Millimeter   |
| Bolt Spacing Maximum          | 11.75 Inch   298.45Millimeter  |
| bore diameter:                | 3.6875 in  |
| bolt center-to-center length: | 10-7/8 in  |
| overall length:               | 14.2500 in   |
| base width:                   | 3-5/16 in  |
| overall height:               | 8.4375 in  |
| expansion type:               | Non-Expansion Bearing (Fixed)  |
| mounting:                     | Two-Bolt Base  |
| finish/coating:               | Uncoated   |
| bearing type:                 | Spherical Roller   |
| seal type:                    | Tri-Guard  |
| bore type:                    | Round  |
| radial dynamic load capacity: | 95000 lbf  |
| housing construction:         | Solid Pillow Block   |

|                              |                     |
|------------------------------|---------------------|
| radial static load capacity: | 110000 lbf          |
| base to bore centerline:     | 4.2500 in           |
| maximum rpm:                 | 1250 RPM            |
| duty type:                   | Standard Duty       |
| lubrication type:            | Lubrication Fitting |
| housing material:            | Cast Iron           |
| series:                      | SYR                 |
| locking device:              | Concentric Collar   |
| replacement bearing:         | 22220               |