

Timken

HM237542/HM237510CD+HM237542XB tapered roller bearings

Shop Timken HM237542/HM237510CD+HM237542XB tapered roller bearings huge N/A Minimum Buy Quantity online discount inventory. and Import machinery parts your car needs with Free Shipping 0.0 Inventory and Free Extended Warranty.

| | |
|---------------------------|-----------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 2.723 lb |
| EAN | 0087796057852 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Eccentric Collar |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 12 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | GRAE30RRB |
| Seals | Double Land Riding Rubber Contact |
| Housing Configuration | 1 Piece Solid |
| Inch – Metric | Metric |

| | |
|-------------------------------|---|
| Other Features | Single Row Spherical Normal Duty High Base With Set Screw |
| Long Description | 2 Bolt Pillow Block; 30MM Bore; 42.9MM Base to Center Height; Eccentric Collar Mount; Ball Bearing; |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | VAS 30 |
| Weight / LBS | 2.72 |
| Nominal Bolt Center to Center | 4.6 Inch 118 Millimeter |
| Actual Bolt Center to Center | 4.6 Inch 117.5Millimeter |
| B | 1.689 Inch 42.9 Millimeter |
| Bolt Spacing Maximum | 0 Inch 0Millimeter |
| Bolt Spacing Minimum | 0 Inch 0Millimeter |
| d | 1.181 Inch 30 Millimeter |
| D | 1.406 Inch 35.7 Millimeter |
| Shaft Size d | 1.181 in |
| Bearing Type | Ball Bearing |
| Inside Ring Outside Diameter | 0.626 in |
| Dimension T | 0.783 in |
| Series | Standard |
| Seal Type | Molded Shroud |
| Base to Center Height H | 42.86 mm |
| Total Length L | 157.2 mm |
| Total Width A | 1.563 in |
| Bolt Hole Spacing J | 117.5 mm |

| | |
|------------------------------|-------------------------------------|
| Bolt Hole Width N | 14.3 mm |
| Bolt Hole Length N1 | 23.8 mm |
| Foot Height H1 | 16.7 mm |
| Total Height H2 | 83.3 mm |
| Dimension L1 | 52.4 mm |
| Inside Ring Width B | =Bearings1_Inside Ring Width= mm |
| Center of Bearing from End S | 8.7 mm |
| Dimension B1 | 1.406 in |
| Static Load Rating | 2530 lbf |
| Dynamic Load Rating | 4850 lbf |