

# Timken        HM911243/HM911216

## tapered roller bearings

Timken HM911243/HM911216 tapered roller bearings manufacturer and global supplier SKF Manufacturer Name of 0.0 Inventory reliable ball and roller ... Timken HM911243/HM911216 tapered roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our targeted industries.

|                                 |                 |
|---------------------------------|-----------------|
| Inventory                       | 0.0             |
| Manufacturer Name               | SKF             |
| Minimum Buy Quantity            | N/A             |
| Weight                          | 0.507           |
| EAN                             | 7316570933161   |
| Product Group                   | B00308          |
| Enclosure                       | 2 Seals         |
| Precision Class                 | ABEC 1   ISO P0 |
| Maximum Capacity / Filling Slot | No              |
| Rolling Element                 | Ball Bearing    |
| Snap Ring                       | Yes             |
| Internal Special Features       | No              |
| Cage Material                   | Steel           |
| Enclosure Type                  | Contact Seal    |
| Internal Clearance              | C0-Medium       |
| Inch – Metric                   | Metric          |

|                          |   |
|--------------------------|---|
| Long Description         | 50MM Bore; 90MM Outside Diameter; 20MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No |
| Other Features           | Deep Groove   NBR Seal   With Snap Ring   |
| UNSPSC                   | 31171504  |
| Harmonized Tariff Code   | 8482.10.50.68   |
| Noun                     | Bearing   |
| Keyword String           | Ball  |
| Manufacturer Item Number | 6210-2RS1NR   |
| Weight / LBS             | 1.117   |
| D                        | 3.543 Inch   90 Millimeter  |
| Inner Race Width         | 0 Inch   0 Millimeter   |
| Outer Race Width         | 0.787 Inch   20 Millimeter  |
| d                        | 1.969 Inch   50 Millimeter  |