

# Timken HM911249/HM911210-B tapered roller bearings

Find the discount Timken HM911249/HM911210-B tapered roller bearings online you need 44,45 Bore Diameter (mm) . We offer ... If you check out our large selection of Timken HM911249/HM911210-B tapered roller bearings once .

Bore Diameter (mm)	44,45
d	44,45 mm
Da	178,5 mm
s1	56,7 mm
A1	39 mm
B1	43,7 mm
G	32,7 mm
H	148,4 mm
J	111 mm
L	15,9 mm
N	14 mm
T	33,2 mm
A2	14 mm
Weight	1,85 Kg
Basic dynamic load rating (C)	21,6 kN
Basic static load rating (C0)	0,915 kN
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.95
EAN	7316576615153

Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	9/16 Inch
Relubricatable	Yes
Insert Part Number	YET 209-112
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	2 Bolt Flange Block; 1-3/4" Bore; 5.8" Bolt Circle; 5-27/32" Bolt Spacing; 1 Piece So
Other Features	Single Row   Standard Duty   Narrow Inner Race   Open End   Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FYT 1.3/4 FM
Weight / LBS	4.3
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Nominal Bolt Circle Diameter Round	5.8 Inch   148 Millimeter

Length Thru Bore	1.719 Inch   43.663 Millimeter
Bore	1.75 Inch   44.45 Millimeter
Bolt Spacing	5.844 Inch   148.438 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter