

Timken

L217845D/L217813+L217813EA

tapered roller bearings

170 Million used Timken L217845D/L217813+L217813EA tapered roller bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and 175 Outer Diameter (mm) location. Order the 140x175x18 Size (mm) with stock ...

Size (mm)	140x175x18
Bore Diameter (mm)	140
Outer Diameter (mm)	175
Width (mm)	18
d	140 mm
D	175 mm
B	18 mm
C	18 mm
r min.	1,1 mm
da min.	146,5 mm
da max	148,5 mm
Da max.	168,5 mm
ra max.	1 mm
Weight	0,832 Kg
Basic dynamic load rating (C)	38,5 kN
Basic static load rating (C0)	48 kN
(Grease) Lubrication Speed	3 400 r/min
Inventory	0.0
Manufacturer Name	NSK

Minimum Buy Quantity	N/A
Weight / Kilogram	0.76
EAN	0029176030376
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	140MM Bore; 175MM Outside Diameter; 18MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6828VV
Weight / LBS	0.88
Bore	5.512 Inch 140 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
Outside Diameter	6.89 Inch 175 Millimeter
bore diameter:	140 mm
closure type:	Double Sealed
outside diameter:	175 mm

internal clearance:	Normal Clearance
overall width:	18 mm
manufacturer upc number:	029176030376
bore type:	Round
SRI	5.34
hidYobi	6828VV
LangID	1
D_	175
SREX	0.025
B_	18
da min	146.5
hidTable	ecat_NSRDGB
SRE	5.34
mass	0.832
GRS rpm	3400
ra	1
SRIX	0.025
D_a	168.5
SRIN	-0.025
C0	48
fo	17.3
SREN	-0.025
DE_	167.819
Prod_Type3	DGBB_SR_VV
DA_	10.319
bomp	0
Z_	26
yobi	6828VV
C_conv	38500

ALPHA_	0
SDM_	157.5
r	1.1
KBRG	6151
SBRG	18
DI_	147.181