

Timken LL521849C/LL521810 tapered roller bearings

Timken LL521849C/LL521810 tapered roller bearings Deal is your source 10 mm d 30 mm D for OEM and accessories. We sell Genuine at discount prices.

d	10 mm
D	30 mm
B	9 mm
rs min	0.6 mm
Radial clearance class	CN
Mass	0.03 kg
Dynamic load, C	5.1 kN
Static load, C ₀	2.39 kN
Fatigue limit load, C _u	0.11 kN
f ₀	13.2
N _{lim} (grease)	25,000 rpm
Min operating temperature, T _{min}	-20 °C
Max operating temperature, T _{max}	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF ₀	3.07 Hz
Characteristic inner ring frequency, BRFI	4.93 Hz
da min	14 mm
Da max	26 mm
ra max	0.6 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.032
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	Special
Inch – Metric	Metric
Long Description	10MM Bore; 30MM Outside Diameter; 9MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.071
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.181 Inch 30 Millimeter
Bore	0.394 Inch 10 Millimeter
Outer Race Width	0.354 Inch 9 Millimeter