

Timken LM229147C/LM229110 tapered roller bearings

Question Timken LM229147C/LM229110 tapered roller bearings ?
Find what you need faster by entering your 50 mm d 90 mm D information .

d	50 mm
D	90 mm
B	20 mm
E	81.5 mm
F	59.5 mm
d1	63.9 mm
rs min	1.1 mm
r1s min	1.1 mm
Radial clearance class	CN
Mass (without HJ ring)	0.5 kg
Dynamic load, C	66 kN
Static load, C0	72 kN
Fatigue limit load, Cu	8.8 kN
Nlim (oil)	8,100 rpm
Nlim (grease)	6,900 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.25 Hz
Characteristic outer ring frequency, BPF0	6.75 Hz
Characteristic inner ring frequency, BRFI	9.25 Hz
da min	56.5 mm

dc min	67 mm
Da max	83.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359665598
Product Group	B04144