Timken M224749/M224710D+M224749XC tapered roller bearings

What are the dimensions of a Timken M224749/M224710D+M224749XC tapered roller bearings? Manufacturing N/A Minimum Buy Quantity Service . Get Your Free, Instant Quote□□ 0.0 Inventory

| Inventory | 0.0 |
|----------------------|---|
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| UNSPSC | 31171536 |
| Weight | 0.85 |
| EAN | 4547359506808 |
| Product Group | M06110 |
| Inner Race Profile | Wide Inner Ring |
| Outer Race Profile | Cylindrical |
| Mounting Method | Eccentric Collar |
| Rolling Element | Ball Bearing |
| Relubricatable | Yes |
| Seal Type | Single Lip Land Riding |
| Snap Ring | Yes |
| Inch — Metric | Inch |
| Long Description | 1-3/4" Bore; Wide Inner Ring; 0.945" Outer Race Width; Cylindrical Outer Race Profile; 3.3 |

| Other Features | Single Row Light Duty Steel Cage With Set Screw Has Flinger |
|-------------------------------|---|
| d | 1.75 Inch 44.45 Millimeter |
| D | 2.217 Inch 56.312 Millimeter |
| Outer Race Width | 0.945 Inch 24.003 Millimeter |
| bore diameter: | 1.7500 in |
| operating temperature range: | -40 to 250 ºF |
| outside diameter: | 3.3465 in |
| fillet radius: | 0.0591 in |
| outer ring width: | 0.8661 in |
| radial dynamic load capacity: | 7300 lbf |
| inner ring width: | 1.6850 in |
| radial static load capacity: | 4600 lbf |
| bore type: | Round |
| bearing material: | Through Hardened Steel |
| locking device: | Eccentric Collar |
| finish/coating: | Uncoated |
| duty type: | Standard Duty |
| seal type: | Contact |
| overall width: | 2.2165 in |
| manufacturer product page: | Click here |