## Timken M236848/M236810 tapered roller bearings

Can't find what you're Mounted Bearing Engineering Group looking for Timken M236848/M236810 tapered roller bearings ? Our expert Representatives be in contact 2-1/2 in Shaft Size with you shortly!

| Engineering Group       | Mounted Bearing       |
|-------------------------|-----------------------|
| Shaft Size              | 2-1/2 in              |
| Shaft Size Type         | Imperial              |
| Full Timken Part Number | QMPL13J208SB          |
| Locking Style           | Eccentric             |
| Weight                  | 22.00 lb              |
| Housing Style           | Two-Bolt Pillow Block |
| UPC Code                | 0883450087629         |
| Dimension A             | 2.75 in               |
| Dimension B             | 5.8 in                |
| Dimension C             | 3.62 in               |
| Dimension D Max         | 7.44 in               |
| Dimension D Min         | 6.81 in               |
| Dimension F             | 9.250 in              |
| Dimension G             | 2.900 in              |
| Dimension H             | 1.38 in               |
| Dimension J (Bolt Size) | 0.625 in              |
| Dimension K             | 1.24 in               |
| Dimension L             | 3.58 in               |
| Dimension M             | 2.13 in               |
| Dimension R             | 0.21 in               |
|                         |                       |

| Dimension S                         | 3.37 in   |
|-------------------------------------|-----------|
| C0 — Static Load                    | 48600 lb  |
| C — Dynamic Load (Basic)            | 46400 lb  |
| e – Geometry Factor                 | 0.24      |
| Y1 – Geometry Factor                | 2.79      |
| Y2 – Geometry Factor                | 4.15      |
| Oil Lubrication - M/N Seal          | 1800 rpm  |
| Oil Lubrication – T Seal            | 3200 rpm  |
| Oil Lubrication – B/C/O Seal        | 1500 rpm  |
| Grease Lubrication – M/N Seal       | 1800 rpm  |
| Grease Lubrication – T Seal         | 2800 rpm  |
| Grease Lubrication – B/C/O Seal     | 1500 rpm  |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0015 in |
| Eng Internal Radial Clearance — Min | 0.0016    |
| Eng Internal Radial Clearance — Max | 0.0026    |
| Pre Install Clearance Min           | 0.0016 in |
| Pre Install Clearance Max           | 0.0026 in |