

Timken

M241547C/M241513D+M241547XA tapered roller bearings

are 40x44x50 Size (mm) a few brands you will find in our inventory. Find Timken M241547C/M241513D+M241547XA tapered roller bearings to see what's in stock!

Size (mm)	40x44x50
Bore Diameter (mm)	40
Outer Diameter (mm)	44
Width (mm)	50
d	40 mm
D	44 mm
B	50 mm
c1 min	0,1 mm
c2 min	0,8 mm
M	– mm
Weight	0,098 Kg
Basic dynamic load rating (C)	156 kN
c1 min.	0.1 mm
c1 max.	0.7 mm
c2 min.	0.8 mm
c2 max.	1.6 mm
$\alpha \pm 8$	20 °
Tolerance shaft	f7
Tolerance housing	H7
Basic dynamic load rating – radial direction C	156 kN

Basic static load rating – radial direction C ₀	490 kN
Specific dynamic load factor K	80 N/mm ²
Specific static load factor K ₀	250 N/mm ²
Factor depending on material and bearing type K _M	480
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2 m/s
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Mass bushing	0.098 kg