

Timken

M919048/M919010D+M919049XC tapered roller bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products at Low Costs. 80x110x16 Size (mm)

| | |
|---------------------|-----------|
| Size (mm) | 80x110x16 |
| Bore Diameter (mm) | 80 |
| Outer Diameter (mm) | 110 |
| Width (mm) | 16 |
| d | 80 mm |
| D | 110 mm |
| B | 16 mm |
| C | 16 mm |
| a | 25 mm |
| b | 2 mm |
| d1 | 90,7 mm |
| r1 min. | 1 mm |
| r2 min. | 1 mm |
| r3 min. | 0,6 mm |
| r5 min. | 0,6 mm |
| C1 | 8,6 mm |
| D1 | 102,2 mm |
| da min. | 84,6 mm |
| Da max. | 105 mm |
| db min | 84,6 mm |
| ra max. | 1 mm |

| | |
|-------------------------------|--------------|
| rb max. | 0,3 mm |
| C2 | 2,7 mm |
| Db max | 105 mm |
| Weight | 0,37 Kg |
| Basic dynamic load rating (C) | 15,6 kN |
| Basic static load rating (C0) | 14,6 kN |
| (Grease) Lubrication Speed | 18 000 r/min |
| (Oil) Lubrication Speed | 28 000 r/min |
| Fatigue load limit (Pu) | 630 |