

# Toyana 20313 KC spherical roller bearings

Manufacturers of all are represented in our partial list of 0.0 Inventory clients. Contact Gary for a complete Toyana 20313 KC spherical roller bearings list of clients and projects.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | IPTCI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.408   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 3   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 3 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 5/16 Inch   |
| Relubricatable            | Yes   |
| Insert Part Number        | SA204-12G   |
| Seals                     | K Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 3 Bolt Flange Block; 3/4" Bore; 2.8" Bolt Circle; 2.4" Bolt Spacing; 1 Piece Solid; E |

|                                    |                                |
|------------------------------------|--------------------------------|
| Other Features                     | Single Row   Narrow Inner Race |
| UNSPSC                             | 31171501                       |
| Harmonized Tariff Code             | 8483.20.40.40                  |
| Noun                               | Bearing                        |
| Keyword String                     | Flanged                        |
| Manufacturer Item Number           | SARFB 204 12 G                 |
| Weight / LBS                       | 0.9                            |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter          |
| D                                  | 1.221 Inch   31.013 Millimeter |
| Nominal Bolt Circle Diameter Round | 2.8 Inch   71 Millimeter       |
| Bolt Spacing                       | 2.4 Inch   61 Millimeter       |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter          |
| d                                  | 0.75 Inch   19.05 Millimeter   |