

# Toyana 22316 CW33 spherical roller bearings

How do I place an EMERGENCY order 30.785 mm Ca for a Toyana 22316 CW33 spherical roller bearings 46.038 mm da that I want to pick up at a our store?

|                         |                |
|-------------------------|----------------|
| da                      | 46.038 mm      |
| Da                      | 100 mm         |
| Ca                      | 30.785 mm      |
| A1                      | 69.85 mm       |
| A2                      | 171.45 mm      |
| S                       | 3.175 mm       |
| ba                      | 26.988 mm      |
| H                       | 133.35 mm      |
| H1                      | 69.85 mm       |
| H2                      | 23.813 mm      |
| J min.                  | 187.325 mm     |
| J max.                  | 209.55 mm      |
| L                       | 244.475 mm     |
| N1                      | 19.05 mm       |
| R1                      | 34.131 mm      |
| R2                      | 15.875 mm      |
| RG                      | 1/8 NPT        |
| PG                      | 1/8 NPT        |
| h                       | 30.163 mm      |
| Housing                 | SAF 511        |
| Bearing                 | 22211 EK       |
| Adapter sleeve assembly | SNW 11×1.13/16 |

|  |                |
|--|----------------|
| Stabilizing ring                       | SR-11-0        |
| Taconite seal                          | TER 22         |
| End plug (suffix Y)                    | EPR 5          |
| Max. speed for Taconite seal           | 1575 r/min     |
| P60°                                   | 44.9 kN        |
| P90°                                   | 27.1 kN        |
| P120°                                  | 17.3 kN        |
| P150°                                  | 15.6 kN        |
| P180°                                  | 19.1 kN        |
| Pa                                     | 4.14 kN        |
| Mass pillow block                      | 7.85 kg        |
| Cap bolt                               | 2 x 1/2-13 UNC |
| Cap bolt recommended tightening torque | 81.3 N·m       |
| Cap bolt, SAE grade                    | 5              |
| Appropriate attachment bolt size G     | 0.625 in       |
| Initial grease fill                    | 39.69 g        |