

# Toyana 230/530 KCW33+AH30/530 spherical roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your Toyana 230/530 KCW33+AH30/530 spherical roller bearings needs 0.0 Inventory – including routine maintenance, major repairs, warranty service, and equipment inspections.

|                           |                           |
|---------------------------|---------------------------|
| Inventory                 | 0.0                       |
| Manufacturer Name         | TIMKEN                    |
| Minimum Buy Quantity      | N/A                       |
| Weight                    | 17.706                    |
| EAN                       | 0883450154543             |
| Product Group             | M06288                    |
| Number of Mounting Holes  | 2                         |
| Mounting Method           | Eccentric Collar          |
| Housing Style             | 2 Bolt Pillow Block       |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel                |
| Expansion / Non-expansion | Non-expansion             |
| Mounting Bolts            | 7/8 Inch                  |
| Relubricatable            | Yes                       |
| Insert Part Number        | 22218                     |
| Seals                     | Triple Lip Nitrile Rubber |
| Housing Configuration     | 1 Piece Solid             |
| Inch – Metric             | Metric                    |
| Other Features            | Double Row                |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 90MM Bore;<br>95MM Base to Center Height;<br>Eccentric Collar Mount;<br>Spherical Roller |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | QMP18J090SM   |
| Weight / LBS                  | 45  |
| Bolt Spacing Minimum          | 9.375 Inch   238.125Millimeter  |
| Bolt Spacing Maximum          | 11.25 Inch   285.75Millimeter   |
| d                             | 3.543 Inch   90 Millimeter  |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter  |
| D                             | 4.03 Inch   102.362 Millimeter  |
| B                             | 3.74 Inch   95 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |