## Toyana 24052 K30CW33+AH24052 spherical roller bearings

Toyana 24052 K30CW33+AH24052 spherical roller bearings Needs Analysis , 0.0 Inventory Manufacturing Service . Get Your Free.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 13.257   |
| EAN                       | 0662461026762  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 7/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 3-211C   |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Single Row   Medium Duty   Has<br>Flinger  |
| Long Description          | 2 Bolt Pillow Block; 2-11/16"<br>Bore; 3-1/2" Base to Center<br>Height; Set Screw Mount; Ball Be |

|                                  | 21171511                        |
|----------------------------------|---------------------------------|
| UNSPSC                           | 31171511                        |
| Harmonized Tariff Code           | 8483.20.40.40                   |
| Noun                             | Bearing                         |
| Keyword String                   | Pillow Block                    |
| Manufacturer Item Number         | MP-43C                          |
| Manufacturer Internal Number     | 704218                          |
| Weight / LBS                     | 29.2                            |
| Bolt Spacing Minimum             | 7.875 Inch   200.025Millimeter  |
| D                                | 3.063 Inch   77.8 Millimeter    |
| В                                | 3.5 Inch   88.9 Millimeter      |
| Bolt Spacing Maximum             | 10.125 Inch   257.175Millimeter |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter            |
| d                                | 2.688 Inch   68.275 Millimeter  |
| Nominal Bolt Center to<br>Center | 9 Inch   229 Millimeter         |