

# Toyana 24056 CW33 spherical roller bearings

Toyana 24056 CW33 spherical roller bearings Engineering Calculator , Manufacturing 0.0 Inventory Service . Get REXNORD Manufacturer Name N/A Minimum Buy Quantity Your Free.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 23.608  |
| EAN                       | 0698210004026   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 5215U   |
| Seals                     | Light Contact   |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Double Collar   Two Auxiliary End Cap   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 2-15/16" Bore; 3-1/2" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | BKPS5215F  |
| Manufacturer Internal Number  | 6800402  |
| Weight / LBS                  | 41.8   |
| d                             | 2.938 Inch   74.625 Millimeter   |
| B                             | 3.5 Inch   88.9 Millimeter   |
| Nominal Bolt Center to Center | 9.8 Inch   248.9 Millimeter  |
| D                             | 4.875 Inch   123.83 Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |
| Actual Bolt Center to Center  | 9.8 Inch   250Millimeter   |