

# Toyana 24156 K30 CW33 spherical roller bearings

offers a Toyana 24156 K30 CW33 spherical roller bearings selection of Genuine 55x140x33 Size (mm) at Wholesale Prices. We are a Toyana 24156 K30 CW33 spherical roller bearings Certified Parts Retailer

Size (mm)	55x140x33
Bore Diameter (mm)	55,000
Outer Diameter (mm)	140,000
Width (mm)	33,000
d	55,000 mm
D	140,000 mm
B	33,000 mm
C	33,000 mm
Contact angle $\alpha$	40 °
rs min	2.1 mm
rls min	1.1 mm
Radial clearance class	CN
Mass	2.69 kg
Dynamic load, C	90.3 kN
Static load, C0	62 kN
Fatigue limit load, Cu	2.8 kN
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	3.95 Hz

Characteristic outer ring frequency, BPF0	4.06 Hz
Characteristic inner ring frequency, BPI	5.94 Hz
da min	311 mm
Da max	128 mm
Db max	133 mm
r1a max	1 mm
ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	2.7
EAN	4547359454468
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch – Metric	Metric

Long Description	55MM Bore; 140MM Outside Diameter; 33MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of B
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7411BG
Weight / LBS	5.945
Width	1.299 Inch   33 Millimeter
Outside Diameter	5.512 Inch   140 Millimeter
Bore	2.165 Inch   55 Millimeter
bore diameter:	55 mm
radial static load capacity:	61800 N
outside diameter:	140 mm
operating temperature range:	-40 to 120 °C
overall width:	33 mm
cage material:	Brass
contact angle:	40 °
outer ring width:	33 mm
row type & fill slot:	Single-Row Non-Fill Slot
maximum rpm:	5200 rpm
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round

precision rating:	ISO Class 0
closure type:	Open
fillet radius:	2.1 mm
snap ring included:	Without Snap Ring
series:	74B
bearing material:	High Carbon Chrome Steel
weight:	2.690 kg
radial dynamic load capacity:	90300 N
manufacturer product page:	<a href="#">Click here</a>