

Toyana 31308 A tapered roller bearings

Request A Quote 50x90x21.75 Size (mm) For Your Special Toyana 31308 A tapered roller bearings Needs Today! Free Quotes. ISO 9001 certified. 50 Bore Diameter (mm)

Size (mm)	50x90x21.75
Bore Diameter (mm)	50
Outer Diameter (mm)	90
Width (mm)	21,75
d	50 mm
D	90 mm
T	21,75 mm
B	20 mm
C	16 mm
a	22,7 mm
r min.	1,5 mm
r2 min.	1,5 mm
da min.	58,5 mm
da max	58 mm
Da min	76 mm
Da max.	81,5 mm
Db min.	86 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,59 Kg
Basic dynamic load rating (C)	77,2 kN
Basic static load rating (C0)	95,8 kN

(Grease) Lubrication Speed	4300 r/min
(Oil) Lubrication Speed	5700 r/min
Calculation factor (e)	0,55
Calculation factor (Y0)	0,6
Bearing No.	30210CR
r(min)	1.5
r1(min)	1.5
Cr	96.7
C0r	95.8
Cu	14.3
Grease lub.	4300
Oil lub.	5700
a(mm)	22.7
da(min)	58.5
db(max)	58
Da(max)	81.5
Da(min)	76
Db(min)	86
Sa(min)	4
Sb(min)	5.5
ra(max)	1.5
rb(max)	1.5
e	0.55
Y1	1.10
Y0	0.60
(Refer.) Mass (kg)	0.590