

# Toyana 32044XM tapered roller bearings

Toyana 32044XM tapered roller bearings Needs Analysis , 6 RoHS Manufacturing Quote Days to Ship Service 190 I.D.(Ø) . Get Your Free.

Days to Ship	Quote
RoHS	6
I.D.(Ø)	190
O.D.(Ø)	340
Width(mm)	92
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Outer Ring Type	Flat
Retainer Type	Momi removing
Rotational Speed(rpm)	1600
Basic Load Rating, Dynamic Rating(N)	1100000
Basic Load Rating, Static Rating(N)	1670000
Clearance sign	No
Accuracy(Class)	Class 0
Bearing Ring Type	Type NU
Acoustic Symbol	No
Holder Symbol	M
Symbol of Bearing Ring Shape	E
Seal, Shield Symbols	No
Precision Grade Symbol	No
Symbol of contact angle	No
Special Configurations Code	No

Symbols of Lubrication Amount	No
Internal Symbol	No
Raceway Ring Shape	Cylindrical Roller
Load Direction	Radial
Inner/Outer Ring Material	Steel
Outer Ring	With Outer Ring
Precision (JIS)	Grade 0
Specifications	Standard
Rolling Element Material	Steel
Holder Color	No
Low Torque Specification	No
Material Symbol	No