

Toyana 33114 A tapered roller bearings

LET OUR 30x62x17.25 Size (mm) Toyana 33114 A tapered roller bearings EXPERTS GET YOU THE PARTS YOU NEED.

| | |
|-------------------------------|-------------|
| Size (mm) | 30x62x17.25 |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 62 |
| Width (mm) | 17,25 |
| d | 30 mm |
| D | 62 mm |
| T | 17,25 mm |
| B | 16 mm |
| C | 12 mm |
| a | 17,8 mm |
| r min. | 1 mm |
| r1 min. | 1 mm |
| da min. | 39 mm |
| Da min | 49 mm |
| Da max. | 56 mm |
| db max. | 36 mm |
| Db min. | 59 mm |
| ra max. | 1 mm |
| rb max. | 1 mm |
| Weight | 0,221 Kg |
| Basic dynamic load rating (C) | 35,5 kN |
| Basic static load rating (C0) | 37 kN |
| (Grease) Lubrication Speed | 5600 r/min |

| | |
|-------------------------|------------|
| (Oil) Lubrication Speed | 7500 r/min |
| Calculation factor (e) | 0,68 |
| Calculation factor (Y0) | 0,49 |
| LangID | 1 |
| outer r | 1 |
| D_ | 62 |
| TC-BET22 | 0 |
| TC-BET21 | 7 |
| TC-BET23 | 0 |
| inner r | 1 |
| mass | 0.221 |
| GRS rpm | 5600 |
| D_b | 59 |
| Cr | 3650 |
| TC-RA | 68.84 |
| DE_ | 52.425 |
| T-ALP23 | 0 |
| db | 36 |
| T-ALP22 | 40 |
| Prod_Type3 | TRBSR_MD_A |
| da | 39 |
| T-ALP21 | 48 |
| Iso | — |
| ALPHA_ | 24.333 |
| SDM_ | 45.13 |
| SBRG | 2 |
| D_a2 | 49 |
| hidYobi | HR30206C |
| Y1 | 0.88 |

| | |
|----------|-------------|
| D_a1 | 56 |
| B_ | 16 |
| hidTable | ecat_NSTPRM |
| Oil rpm | 7500 |
| C0r | 3800 |
| Y0 | 0.49 |
| TC-SLR | 10.5 |
| inner ra | 1 |
| outer rb | 1 |
| C0 | 37 |
| Sa | 2 |
| Sb | 5 |
| e | 0.68 |
| DA_ | 7.77 |
| Z_ | 15 |
| C_ | 12 |
| yobi | HR30206C |
| TC-DA1 | 8.403 |
| TC-DA2 | 7.136 |
| KBRG | 3111 |
| DI_ | 37.834 |