

Toyana 33221 A tapered roller bearings

Enjoy High Margins on Competitive 65x120x23 Size (mm) 120 Outer Diameter (mm) Pricing.Great Wholesale Products at Low Costs.

Size (mm)	65x120x23
Bore Diameter (mm)	65
Outer Diameter (mm)	120
Width (mm)	23
d	65 mm
D	120 mm
B	23 mm
C	23 mm
Angle (α)	30 °
a	15.2 mm
r min.	1.5 mm
r1 min.	1 mm
2B	46 mm
da min.	70 mm
Da max.	114.6 mm
ra max.	1 mm
Weight	1.02 Kg
Basic dynamic load rating (C)	114 kN
Basic static load rating (C0)	116 kN
(Grease) Lubrication Speed	3900 r/min
Bore Type	Cylindrical Bore
Enclosure	Open

Configuration	Duplex
Bore Size	65 mm
Outside Diameter	120 mm
Width	23 mm
Fillet Radius/Chamfer	1.5 mm
r1	1 mm
Dynamic Load Rating	114,000 N
Static Load Rating	116,000 N
Limiting Speed – Grease	3,900 rpm
Limiting Speed – Oil	5,300 rpm
da1 (min)	74 mm
da2 (min)	70 mm
Da1 (max)	111 mm
Da2 (max)	114.6 mm
ra (max)	1.5 mm
ra1 (max)	1 mm