

Toyana 497A/492A tapered roller bearings

YOU'LL 70 mm da FIND AN EXTENSIVE SELECTION 82.55 mm db OF Toyana 497A/492A tapered roller bearings FOR SALE.

da	70 mm
db	82.55 mm
dc	66.675 mm
Da	150 mm
Ca	60.808 mm
A1	88.9 mm
A2	136.525 mm
ba	34.131 mm
H	187.325 mm
H1	95.25 mm
H2	33.337 mm
J min.	250.825 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	39.688 mm
Housing	FSAF 314
Bearing	1314

Lock nut	N 14
Lock washer	W 14
Stabilizing ring	2 x SR-1614
Labyrinth ring (db shaft position)	LOR 64
Labyrinth ring (dc shaft position)	LOR 43
End plug (suffix Y)	EPR 8
Bearing limiting speed	6000 r/min
P60°	92.5 kN
P90°	55.6 kN
P120°	34.7 kN
P150°	30.7 kN
P180°	37.8 kN
Pa	24.5 kN
Mass pillow block	18.2 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	175.77 g