

# Toyana 7012 A-U0 angular contact ball bearings

Welcome to the 69.85 mm da Toyana 7012 A-U0 angular contact ball bearings 140 mm Da online seller.

da	69.85 mm
Da	140 mm
Ca	42.799 mm
A1	88.9 mm
A2	126.603 mm
S	4.763 mm
ba	34.131 mm
H	169.863 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
L	330.2 mm
N1	22.225 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	31.75 mm
Housing	SAF 516
Bearing	22216 EK
Adapter sleeve assembly	SNW 16×2.3/4
Stabilizing ring	SR-16-13

Labyrinth ring	2 x LOR 45
PosiTrac Plus contact element	2 x B10724-44
End plug (suffix Y)	EPR 8
Max. speed for PosiTrac Plus seal	2150 r/min
P60°	83.2 kN
P90°	49.8 kN
P120°	30.2 kN
P150°	26.7 kN
P180°	31.6 kN
Pa	7.83 kN
Mass pillow block	16.3 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	87.885 g