

# Toyana 7030 C-UD angular contact ball bearings

170 Million used Toyana 7030 C-UD angular contact ball bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and location. N/A Minimum Buy Quantity Order the 0.0 Inventory REXNORD Manufacturer Name with stock ...

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.257   |
| EAN                       | 0662327723385   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | UG331L  |
| Seals                     | Steel Clad Clearance  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Single Row   Heavy Duty   Single Collar   Standard Backing   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-15/16" Bore; 3-1/8" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | PU331K5  |
| Manufacturer Internal Number  | 5872338  |
| Weight / LBS                  | 17.2   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| d                             | 1.938 Inch   49.225 Millimeter   |
| B                             | 3.125 Inch   79.38 Millimeter  |
| D                             | 2.813 Inch   71.45 Millimeter  |
| Actual Bolt Center to Center  | 8.9 Inch   225.4Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |
| Nominal Bolt Center to Center | 8.9 Inch   226 Millimeter  |