

Toyana 71910 C-UX angular contact ball bearings

Online shopping Toyana 71910 C-UX angular contact ball bearings from a great selection 12 mm d at Store. 8 mm B ... Accessories.

d	12 mm
D	28 mm
B	8 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.02 kg
Dynamic load, C	5.1 kN
Static load, C ₀	2.39 kN
Fatigue limit load, C _u	0.11 kN
f ₀	13.2
N _{lim} (grease)	16,700 rpm
Min operating temperature, T _{min}	-20 °C
Max operating temperature, T _{max}	80 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF ₀	3.07 Hz
Characteristic inner ring frequency, BPFI	4.93 Hz
da min	14 mm
da max	16 mm

Da max	26 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.021
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Riveted Cage
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	12MM Bore; 28MM Outside Diameter; 8MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Prelubricated Solid Grease
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.0546

Outer Race Width	0.315 Inch 8 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.102 Inch 28 Millimeter
Bore	0.472 Inch 12 Millimeter