

Toyana 7230 A-UX angular contact ball bearings

How N/A Minimum Buy Quantity do I place an EMERGENCY order for 0.0 Inventory a Toyana 7230 A-UX angular contact ball bearings that I want to pick up at a our store?

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.447
EAN	7316570894554
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polyamide
Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 27MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Double

Other Features	Glass Fibre Reinforced Cage MT33-Lithium Soap Thickener Grease
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	3207 A-2ZTN9/MT33
Weight / LBS	1.0196
d	35 mm
B	27 mm
D	72 mm
bore diameter:	35 mm
maximum temperature:	257 °F
outside diameter:	72 mm
cage material:	Polyamide 66
overall width:	27 mm
maximum rpm:	9000 rpm
contact angle:	30 °
finish/coating:	Uncoated
row type & fill slot:	Double-Row Non-Fill Slot
fillet radius:	1.1 mm
bore type:	Round
series:	3200
closure type:	Double Shielded
weight:	0.97 lb
bearing material:	Steel
manufacturer product page:	Click here
radial dynamic load capacity:	40 kN

manufacturer upc number:	7316570894554
radial static load capacity:	28 kN
d2 ≈	45.4 mm
D2 ≈	63.85 mm
r1,2 min.	1.1 mm
a	42 mm
da min.	42 mm
da max.	45 mm
Da max.	65 mm
ra max.	1 mm
Basic dynamic load rating C	40 kN
Basic static load rating C0	28 kN
Fatigue load limit Pu	1.18 kN
Reference speed	10000 r/min
Limiting speed	9000 r/min
Calculation factor kr	0.06
Calculation factor e	0.8
Calculation factor X	0.63
Calculation factor Y0	0.66
Calculation factor Y1	0.78
Calculation factor Y2	1.24
Mass bearing	0.44 kg