

Toyana 7234 B-UX angular contact ball bearings

Toyana 7234 B-UX angular contact ball bearings, Units 82.804 mm Ca and 136.525 mm da Housings CAD models , Manufacturing Service . Get Your Free. 269.999 mm Da

da	136.525 mm
Da	269.999 mm
Ca	82.804 mm
A1	158.75 mm
A2	215.9 mm
S	4.763 mm
ba	65.088 mm
H	320.675 mm
H1	160.325 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SAF 530
Bearing	22230 CCK/W33

Adapter sleeve assembly	SNW 30×5.3/8
Stabilizing ring	SR-30-0
Labyrinth ring	2 x LOR 128
End plug (suffix Y)	EPR 16
Bearing limiting speed	3000 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	32.7 kN
Mass pillow block	91.6 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g