

# Toyana 7305 B-UX angular contact ball bearings

What is Toyana 7305 B-UX angular contact ball bearings in mechanical engineering? Manufacturing Service 0.0 Inventory . Upload your CAD file for an instant.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.988  |
| EAN                       | 0883450112031  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22216  |
| Seals                     | Double Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut  |
| Long Description          | 4 Bolt Pillow Block; 2-3/4" Bore; 3-1/4" Base to Center Height; V Lock Mount; Spherical Ro |

|                               |                               |
|-------------------------------|-------------------------------|
| UNSPSC                        | 31171511                      |
| Harmonized Tariff Code        | 8483.20.40.80                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Manufacturer Item Number      | QVPF16V212SB                  |
| Weight / LBS                  | 22                            |
| B                             | 3.25 Inch   82.55 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |
| d                             | 2.75 Inch   69.85 Millimeter  |
| D                             | 3.29 Inch   83.566 Millimeter |
| Bolt Spacing Maximum          | 9.1 Inch   231.14Millimeter   |
| Bolt Spacing Minimum          | 7.6 Inch   193.04Millimeter   |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter   |