

Toyana 7319AC angular contact ball bearings

Toyana 7319AC angular contact ball bearings Product Brochures , Manufacturing Service . Get Your 106.362 mm da Free.

da	106.362 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
ba	46.831 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	65.088 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	40.481 mm
Housing	SAFS 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024×4.3/16
Stabilizing ring	2 x 38151-24

Labyrinth ring	2 x LOR 113
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1350 r/min
P60°	175 kN
P90°	105 kN
P120°	64.9 kN
P150°	58.7 kN
P180°	71.2 kN
Pa	16.7 kN
Mass pillow block	38.6 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g