

# Toyana CX211 wheel bearings

Our highly-skilled and 42x30x7 Size (mm) factory-trained 30 Outer Diameter (mm) service experts have the resources to help you with all your Toyana CX211 wheel bearings needs – including routine maintenance, major repairs, warranty service, and equipment inspections.

Size (mm)	42x30x7
Bore Diameter (mm)	42
Outer Diameter (mm)	30
Width (mm)	7
d	30 mm
D	42 mm
B	7 mm
d1	33.11 mm
D2	39.2 mm
r1,2 – min.	0.3 mm
da – min.	32 mm
da – max.	33 mm
Da – max.	40 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	3.6 kN
Basic static load rating – C0	2.9 kN
Fatigue load limit – Pu	0.125 kN
Limiting speed	9500 r/min
Calculation factor – kr	0.02
Calculation factor – f0	14.1
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	7316572094761
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 42MM Outside Diameter; 7MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No F
Other Features	Deep Groove   NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	W 61806-2RS1
Weight / LBS	0.054
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Outside Diameter	1.654 Inch   42 Millimeter
Bore	1.181 Inch   30 Millimeter
d1 ≈	33.11 mm

D2 ≈	39.2 mm
r1,2 min.	0.3 mm
da min.	32 mm
da max.	33 mm
Da max.	40 mm
ra max.	0.3 mm
Basic dynamic load rating C	3.58 kN
Basic static load rating C0	2.9 kN
Fatigue load limit Pu	0.125 kN
Calculation factor kr	0.02
Calculation factor f0	14.1
Mass bearing	0.024 kg