

Toyana CX478 wheel bearings

High Quality Toyana CX478 wheel bearings. Competitive Pricing. Accept Small Order. Easy and Fast 25 Bore Diameter (mm) Shipping.

| | |
|-------------------------------|---------------|
| Bore Diameter (mm) | 25 |
| Width (mm) | 34,1 |
| d | 25 mm |
| Da | 60 mm |
| A1 | 2 mm |
| B | 34,1 mm |
| G | 8 mm |
| H | 95 mm |
| H1 | 34 mm |
| J | 76 mm |
| L | — |
| N | 8,7 mm |
| T | 21,8 mm |
| A2 | 9 mm |
| Weight | 0,33 Kg |
| Basic dynamic load rating (C) | 14 kN |
| Basic static load rating (C0) | 7,8 kN |
| Housing material | Pressed steel |
| B4 | 5 mm |
| Da min. | 56 mm |
| s1 | 19.8 mm |
| Basic dynamic load rating C | 14 kN |
| Basic static load rating C0 | 7.8 kN |

| | |
|---|-------------|
| Fatigue load limit Pu | 0.335 kN |
| Permissible radial housing load max. | 3.6 kN |
| Mass unit | 0.29 kg |
| Thread grub screw G2 | M6x0.75 |
| Hexagonal key size for grub screw N | 3 mm |
| Recommended tightening torque for grub screw | 4 N·m |
| Recommended diameter for attachment bolts, mm G | 8 mm |
| Recommended diameter for attachment bolts, inch G | 0.3125 in |
| Bearing | YAR 205-2RF |
| Housing | PFD 52 |