

Toyana CX546 wheel bearings

How do I Mounted Bearing Engineering Group place an EMERGENCY order for a Toyana CX546 wheel bearings that I want to pick up at a our store?

| | |
|-------------------------|--------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 1-15/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QMCW10J115SB |
| Locking Style | Eccentric |
| Weight | 10 lb |
| Housing Style | Piloted Flange Cartridge |
| UPC Code | 0883450061926 |
| Dimension BC | 5.38 in |
| Dimension C | 2.760 in |
| Dimension E | 3.80 in |
| Dimension B Fix | 1.54 in |
| Dimension B Exp | 1.62 in |
| Dimension F | 6.38 in |
| Dimension D | 4.47 in |
| Dimension H | 0.38 in |
| Dimension J (Bolt Size) | 0.438 in |
| Dimension M | 1.89 in |
| Dimension R | 0.17 in |
| Dimension S | 2.87 in |
| Dimension G | 4.500 in |
| Dimension K | 0.98 in |
| Dimension L Exp | 3.12 in |

| | |
|-------------------------------------|-----------|
| Dimension L Fix | 3.04 in |
| Dimension N | 1.50 in |
| C0 – Static Load | 26600 lb |
| C – Dynamic Load (Basic) | 26300 lb |
| e – Geometry Factor | 0.24 |
| Y1 – Geometry Factor | 2.84 |
| Y2 – Geometry Factor | 4.23 |
| Oil Lubrication – M/N Seal | 2400 rpm |
| Oil Lubrication – T Seal | 4200 rpm |
| Oil Lubrication – B/C/O Seal | 1800 rpm |
| Grease Lubrication – M/N Seal | 2400 rpm |
| Grease Lubrication – T Seal | 3550 rpm |
| Grease Lubrication – B/C/O Seal | 1800 rpm |
| Float | 0.050 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0016 |
| Eng Internal Radial Clearance – Max | 0.0026 |
| Pre Install Clearance Min | 0.0016 in |
| Pre Install Clearance Max | 0.0026 in |