

# Toyana GE 460 QCR plain bearings

What are 0.0 Inventory the types of Toyana GE 460 QCR plain bearings ? Manufacturing Service . Get Your Free, Instant TIMKEN Manufacturer Name price, design review.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 22.7   |
| EAN                       | 0883450351133  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                                      |
| Housing Style             | 2 Bolt Pillow Block                                    |
| Rolling Element           | Spherical Roller Bearing                               |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 24 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Teflon Labyrinth                                       |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Collar   SN Style   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 3-1/2" Bore; 4.409" Base to Center Height; Concentric Collar Mount; S |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Weight / LBS                  | 56   |
| Bolt Spacing Minimum          | 11.417 Inch   290Millimeter  |
| B                             | 4.409 Inch   112 Millimeter  |
| D                             | 5.197 Inch   132 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Nominal Bolt Center to Center | 12.1 Inch   308.5 Millimeter   |
| Bolt Spacing Maximum          | 12.874 Inch   327Millimeter  |
| d                             | 3.5 Inch   88.9 Millimeter   |